

	DISCO ¹	3600 FRC MOVE	3600 FC MOVE	3600 F MOVE	3200 FRC MOVE	3200 FC MOVE	3200 F MOVE	3600 FRC PROFIL	3600 FC PROFIL	3600 F PROFIL	3200 FRC PROFIL	3200 FC PROFIL	3200 F PROFIL	3150 F	4000 CONTOUR	3600 RC CONTOUR	3600 / 3600 C CONTOUR	3200 RC CONTOUR	3200 / 3200 C CONTOUR	2800 RC CONTOUR	2800 / 2800 C CONTOUR	3550	3150 C	3150	2750 RC	2750 C	2750	290	250	210 RC	210	
Front mowers														Centrally suspended CONTOUR rear mowers						Side-mounted rear mowers						Rear mowers with inline mower bar						
Dimensions and weights																																
Working width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.00	3.40	3.40	3.00	3.00	3.00	3.00	3.80	3.40	3.40	3.00	3.00	2.60	2.60	3.40	3.00	3.00	2.60	2.60	2.60	2.85	2.45	2.10	2.10	
Hitch category		II	II	II	II	II	II	II	II	II	II	II	II	III	III	II / III	III	II / III	II	II	II	II	II	II	II	II	II	II	II	II		
PTO shaft speed	rpm	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	540 (460)	540 (460)	540 (460)	540	540	540	540		
Transport width	m	3.40	3.40	3.40	3.00	3.00	3.00	3.40	3.40	3.40	3.00	3.00	3.00	3.00	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Machine height	m	–	–	–	–	–	–	–	–	–	–	–	–	3.90	3.57	3.57	3.19	3.19	2.86	2.86	3.87	3.70	3.70	3.29	3.29	3.29	3.40	3.00	2.65	2.65		
Weight (according to conditioner)	approx. kg	1420	1390	1060	1250	1220	970	685	1195	870	1040	1010	775	685	1040	1300	950 / 1280	1180	870 / 1150	1070	810 / 1050	845	1130	785	1060	1040	725	630	600	880	560	
Mower																																
MAX CUT mower bar ²		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–		
ACTIVE FLOAT suspension		● ³	● ³	● ³	● ³	● ³	● ³	○ ³	○ ³	○ ³	○ ³	○ ³	○ ³	●	●	●	●	●	●	●	–	–	–	–	–	–	–	–	–	–		
Discs (2 knives per disc)		8	8	8	7	7	7	8	8	8	7	7	7	7	9	8	8	7	7	6	6	8	7	7	6	6	6	7	6	5	5	
Quick knife change		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	–	–	–	–		
Conditioner																																
Conditioner speed	rpm	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	950	900 / 770	–	–	–	940	– / 910	940	– / 910	940	– / 910	–	900	–	900	900	–	–	–	940	–	
Hydraulics																																
Hydraulic spool valves		1 sa (+1 da4 + 1sa3)						(1 da4 + 1sa3)						1 x da5 (+1da4 +1 sa3)				1 x da ⁵ (+ 1 x sa3)						1 x sa								
Equipment																																
Hydraulically foldable protective side covers		○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	○ ⁴	–	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Wide crop spreader		–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–/○	–	–/○	–	–/○	–	○	–	–	○	–	–	–	–	–	
Adjustable swathing plates		●	●	–	●	●	–	●	●	–	●	●	–	–	–	●	–/●	●	–/●	●	–/●	–	●	–	●	●	–	–	–	●	–	
Outside swathing disc		–	–	● (2 x)	–	–	● (1 x)	–	–	● (2 x)	–	–	● (1 x)	● (1 x)	○	–	○/–	–	○/–	–	○/–	○	–	○	–	–	○	–	–	–	–	
High-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Twin high-cut skids		○	○	○	○	○	○	○	○	○	○	○	○	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	
Wear skids		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
Bar protection device (for intensive use conditions)		○	○	○	○	○	–	○	○	○	○	○	–	–	–	○	–/○	○	–/○	○	–/○	–	–	–	–	–	–	–	–	–	–	
Warning signs with lighting		○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○ ⁶	○	○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	
Double mirror		○	○	○	○	○	○	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	
Hydraulic transport locking device		–	–	–	–	–	–	–	–	–	–	–	–	–	○	○	○	○	○	○	○	–	–	–	–	–	–	–	–	–	–	
Mechanical breakback protection		–	–	–	–	–	–	–	–	–	–	–	–	–	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	

¹ C = tine conditioner, RC = roller conditioner, F = front, T = trailed, no suffix = without conditioner

² Standard mowing height 40 mm (continuously adjustable, 30–70 mm)

³ 1 x sa required for setting the ACTIVE FLOAT pressure

⁴ 1 x da required for the hydraulic folding of the protective cover

⁵ With float position

⁶ Folding

● Standard ○ Option – Not available

● Standard ○ Option – Not available

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.

3600 TRC CONTOUR	3600 TC CONTOUR	3200 TRC CONTOUR	3200 TC CONTOUR	3200 TC AUTOSWATHER	3150 TRC	3150 TC	3150 TC FLATGRÖUPE
---------------------	--------------------	---------------------	--------------------	------------------------	----------	---------	-----------------------

**Trailed mowers with CONTOUR
central drawbar**

3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00
1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850)	1000 (850) / 540 (460)	1000 (850) / 540 (460)	1000 (850) / 540 (460)
3.40	3.40	3.00	3.00	3.00	3.00	3.00	3.00
–	–	–	–	–	–	–	–
2380	2320	2300	2230	2430	1900	1750	1900

Trailed mowers with side drawbar

●	●	●	●	●	●	●	●
●	●	●	●	●	–	–	–
8	8	7	7	7	7	7	7
●	●	●	●	●	●	●	●

1050	1080 / 900	1050	1080 / 900	1200	1033	900 / 770	1033
------	---------------	------	---------------	------	------	-----------	------

1 x sa + 1 x da (+ 1 x sa ³)	2 x sa + 1 x da (+ 1 x sa ³)	1 x sa + 1 x da
--	--	-----------------

–	–	–	–	–	–	–	–
–	○	–	○	○	–	○	–
●	●	●	●	●	●	●	●
–	–	–	–	–	–	–	–
○	○	○	○	○	○	○	○
–	–	–	–	–	–	–	–
○	○	○	○	○	○	○	○
○	○	○	○	○	–	–	–
●	●	●	●	●	●	●	●
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–
–	–	–	–	–	–	–	–